

Serial No. 10/720,085

**IN THE CLAIMS**

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strike through~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please **AMEND** the claims in accordance with the following:

1. (CURRENTLY AMENDED) A personal identification terminal comprising:  
a plurality of identification conditions including identification means and identification levels that are selectable for use; and  
means for selecting one of the plural identification conditions to perform identification according to in accordance with identification condition setting information ~~that is received~~ from a server every time ~~when receiving a request for identification~~ is received from the server,  
wherein the identification condition setting information received from the server includes a digital signature for detecting an alteration thereof; and  
means for sending to the server, as a confirmation, identification condition used condition ~~information that indicates one of the identification conditions, which was used~~ by the personal identification terminal for the identification, in a format enabling detection of an alteration thereof, together with a result of the identification.
2. (Cancelled)
3. (Previously Presented) A personal identification terminal according to claim 1, wherein if the identification condition that is designated by the identification condition setting information does not exist, default identification condition is used so as to perform the personal identification.
4. (Cancelled)

Serial No. 10/720,085

5. (Previously Presented) A personal identification terminal according to claim 1, wherein the format that enables detection of an alteration is based on a network authentication protocol utilizing a secret key.

6. (Previously Presented) A personal identification terminal according to claim 5, wherein different secret keys are used for different identification conditions.

7. (Previously Presented) A personal identification terminal according to claim 1, wherein the used condition information is added to information of the result of the identification, which is enciphered or provided with a digital signature before being sent to the server.

8. (Previously Presented) A personal identification terminal according to claim 1, wherein in the case where identification means utilizing biometric information is used, a score indicating a similarity or a hash value of the score is added to the information of the result of the identification.

9. (Previously Presented) A personal identification terminal according to claim 1, further comprising a next identification means decision portion for deciding identification means utilizing biometric information that should be used next in accordance with a score that indicates a similarity when the identification was performed using identification means utilizing biometric information.

10. (Original) A personal identification terminal according to claim 9, wherein if the score that indicates a similarity when the identification was performed using identification means utilizing biometric information is lower than a predetermined minimum level, the process is stopped without proceeding to the next identification process.

Serial No. 10/720,035

11. (Previously Presented) A personal identification terminal according to claim 1, wherein if the score that indicates a similarity when the identification was performed using identification means utilizing biometric information shows complete identity, the result of the identification is regarded as being false.

12. (Original) A personal identification terminal according to claim 1, wherein a combination of an IC card and an IC card reader/writer constitutes the terminal.

13. (CURRENTLY AMENDED) A server that is connected to a personal identification terminal including a plurality of identification conditions including identification means and identification levels that are selectable for use, the server comprising a programmed computer processor controlling the server according to a process comprising:

sending to the personal identification terminal identification condition setting information for designating one of the plural identification conditions of identification means and identification levels to be selected by the personal identification terminal to perform identification, every time a request for identification is sent from the server to the personal identification terminal;

storing a log of a score that indicates a similarity, if the personal identification terminal performed the identification using biometric information, or a hash value of the score, that was added to result information of a result of identification, the identification received from the personal identification terminal according to the sending of the identification condition setting information, ~~received from the personal identification terminal~~; and

~~deciding that identification is failed when the~~ failing the identification, if same score value continues several times in accordance with the read log of the score or the hash value of the score, despite ~~the~~ result of the identification received from the personal identification terminal.

14. (CURRENTLY AMENDED) A method of personal identification comprising:

sending by a server identification condition setting information together with a request for identification ~~from a server to a personal identification terminal~~ including a plurality of identification conditions including identification means and identification levels that are selectable for use by the personal identification terminal to perform the identification;

Serial No. 10/720,085

selecting by the personal identification terminal one of the plural identification conditions ~~by the personal identification terminal in accordance with~~ to perform identification, according to the identification condition setting information ~~that is received from the server; and~~

sending by the personal identification terminal to the server, as a confirmation, ~~identification condition~~ used ~~condition information that indicates one of the identification~~ conditions ~~that was used for the identification from~~ by the personal identification terminal for the ~~identification, to the server~~ in a format that enables detection of an alteration thereof together with a result of the identification.

15. (CURRENTLY AMENDED) The method according to claim 14, further comprising:

sending identification terminal information including a location and a current time from the personal identification terminal to the server, before sending the request for identification and the identification condition setting information from the server to the personal identification terminal; and

changing the identification condition setting information to be sent to the personal identification terminal by a processing portion of the server in accordance with the identification terminal information that was received from the personal identification terminal.

16. (CURRENTLY AMENDED) The method according to claim 14, further comprising sending information for designating a number of usable times of a secret key, together with the request for identification and the identification condition setting information sent from the server to the personal identification terminal, ~~so as to limit the~~ number of usable times ~~a user can use~~ of the secret key by a user, when a result of the identification is OK.

17. (CURRENTLY AMENDED) A computer program that is installed in a personal identification terminal having a plurality of identification conditions including identification means and identification levels that are selectable for use, the computer program makes a processor of the personal identification terminal execute a process comprising:

selecting one of the plural identification conditions ~~in accordance with~~ to perform identification, according to identification condition setting information ~~that is received from a~~ server every time ~~when receiving a request for identification~~ is received from the server; and

Serial No. 10/720,085

sending, ~~as a confirmation, used identification condition information that indicates one of the identification conditions that was used by the personal identification terminal~~ for the identification to the server, in a format that enables detection of an alteration thereof, together with a result of the identification.

18. (CURRENTLY AMENDED) A computer readable storage medium storing a computer program that is installed in a server communicably connectable to a personal identification terminal having a plurality of identification conditions including identification means and identification levels that are selectable for use, the computer program makes a processor of the ~~personal identification terminal~~server execute a process comprising:

~~selecting one of the plural identification conditions in accordance with identification condition setting information that is received from a server every time when receiving a request for identification from the server; and~~

~~sending used condition information that indicates one of the identification conditions that was used for the identification to the server in a format that enables detection of an alteration thereof together with a result of the identification to the personal identification terminal~~  
identification condition setting information for designating one of the plural identification conditions of identification means and identification levels to be selected by the personal identification terminal to perform identification, every time a request for identification is sent from the server to the personal identification terminal;

storing a log of a score that indicates a similarity, if the personal identification terminal performed the identification using biometric information, or a hash value of the score, that was added to result information of the identification received from the personal identification terminal according to the sending of the identification condition setting information; and

failing the identification, if same score value continues several times in accordance with the read log of the score or the hash value of the score, despite a result of the identification received from the personal identification terminal.